





The clean, contemporary shape of Glacier complements any kitchen design. This new design has features like the quiet Captur™ system and brilliant halogen lighting.

SIZE	BISQUE	BLACK	STAINLESS	WHITE	GREASE FILTERS (replacement)	NON-DUCTED FILTERS
24 in.		BCSD124BL	BCSD124SS	BCSD124WW	HPFA124 (Type "B1")	HPF24 (Type "Xb")
30 in.	BCSD130BC	BCSD130BL	BCSD130SS	BCSD130WW	HPFA130 (Type "C1")	HPF30 (Type "Xc")
36 in.	BCSD136BC	BCSD136BL	BCSD136SS	BCSD136WW	HPFA136 (Type "D1")	HPF36 (Type "Xd")
42 in.		BCSD142BL	BCSD142SS	BCSD142WW	HPFA142 (Type "E1")	HPF42 (Type "Xe")

HVI PERFORMANCE							
			Soi	nes		CFM	
Duct Orientation	Size	Damper	Normal	High	Normal	High 0.25 in. w.g.	High 0.1 in. w.g.
Vertical - Rectangular	3¼ in. x 10 in.	Included	1.5	5.0	130	130	220
Horizontal - Rectangular	3¼ in. x 10 in.	Included	1.5	5.0	110	128	210
Round - Vertical	7 in.	Sold Separately	1.5	5.0	150	110	240

FEATURES			
Max. Blower CFM*	300		
Control type	2-speed Rocker		
Delay off	no		
Filter Clean Reminder	no		
Heat Sentry™	no		
ADA Capable	yes		
Lighting	2-level 50 W Halogen (not included)		
Grease Filters	Open Mesh (Qty. 2)		
Installation Hardware	EZ1 brackets		
ENERGY STAR®	no		
Recirculation	Non-ducted filters sold separately		

AC INPUT

120 V, 60 Hz - 1.4 AMPS

OPTIONAL ACCESSORIES					
7-in. Round Damper	BP87Q				
Make-up Air Dampers	MD6TU, MD8TU and MD10TU				


MOUNTING HEIGHT

18 in. to 24 in. from cooktop to bottom of hood


LIMITED WARRANTY

1-year (See installation manual for full warranty text.)

FOR INDOOR USE ONLY







HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 and 0.25 in. static pressure at high speed based on tests conducted in an HVI-approved state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

99045740E

- BCSD1 SERIES

^{*} Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure.