# SWASH BL67 Advanced bidet seat





BL76-EW / BL67-RW Elongated White / Round White Discover a whole new level of better bathroom hygiene with Swash BL67 and the complete feature set of an advanced bidet seat. Comes with all parts for a standard installation, including a % inch metal T-valve and a 25 inch metal braided bidet hose with ½ inch connectors.

### **TECHNICAL SPECIFICATIONS**

BL67-EW / BL67-RW
120V/60Hz
870W
9.95 psi – 106.7 psi
Elongated: 18.5 in x 20.7 in x 5.7 in / Round: 18.5 in x 19.5 in x 5.7 in
3.9 ft
Elongated: 11.24 lbs / Round: 10.8 lbs
37.4°F – 104°F
330 lbs
160 lbs
Elongated: 11.9 in x 8.1 in / Round: 10.6 in x 8.1 in
0.51 in x 0.44 in diameter









## HEATED SEAT SPECIFICATIONS

Seat Temperature Control	<b>4 levels:</b> Off – room temperature, Low – 93.2°F, Medium – 100.4°F, High – 107.6°F
Max Heater Power Consumption	55W
Safety Devices	Thermostat, Thermal Fuse, Thermal Sensor, Seat Occupied Sensor

## WARM WATER WASHING DEVICE

Rear Wash	Maximum 0.8 L/min., automatic nozzle self-cleaning
Front Wash	Maximum 0.8 L/min., automatic nozzle self-cleaning
Strong Wash	Maximum 0.6 L/min., automatic nozzle self-cleaning
Standard Time	Rear Wash: 2 minutes / Front Wash: 2 minutes / Strong Wash: 2 minutes
Water Pressure Control	5 levels
Water Temperature Control	<b>4 levels:</b> Off – incoming water temp., Low – 91.4°F, Medium – 96.8°F, High – 102.2°F
Max Heater Power Consumption	800W
Safety Devices	Thermal Fuse, Thermostat, Water Level Sensor, Thermal Sensor, Bi-metal

#### HYGIENE


- Rear, Front, and Strong wash
- Stainless-steel nozzle
- Positionable nozzle
- Adjustable water pressure
- Adjustable water temperature
- Nozzle oscillation

#### COMFORT

- Gentle Wash function
- Ergonomic heated seat with adjustable temperature
- Massage and pulse
- Continuous heated water

#### CONVENIENCE

- Illuminating nightlight
- Dual Eco Mode for energy savings
- Sidearm control panel
- Gentle-closing seat and lid
- Quick release seat



- A. Center of bolt holes to front of toilet bowl Elongated Swash models: 18"—19.5" Round Swash models: 16"—17.75"
- **B.** Distance from center of bolt holes to toilet seat tank All models: Minimum 1.5"
- C. Distance between bolt holes All models: 5.25"—7.45"

