

## WASHLET® S1 ELONGATED

### FEATURES

- Electronic bidet seat
- Self-cleaning wand cleans itself inside and out before and after every use
- CLEAN RESIN® keeps wand and seat cleaner, more hygienic, and effortless to maintain
- Gentle aerated, warm water, front and rear spray with oscillating and pulsating features
- Adjustable spray position, water temperature, and water pressure
- Instantaneous water heater for continuous warm water and energy savings
- Convenient arm control panel
- Heated seat with temperature control
- Seamless seat design eliminates the gap where dirt collects
- SoftClose® seat
- Docking station for easy cleaning and installation
- Auto energy saver mode adjusts the seat temperature when inactive
- Compatible with most elongated toilets



### MODELS

- SW2326#01

### COLOR/FINISHES

- #01 Cotton

### PRODUCT SPECIFICATION

Seat shall have gentle aerated, warm water, dual action spray with oscillating features. Seat shall have adjustable water temperature and volume. Seat shall include convenient arm control panel. Seat shall include power cord, and water supply hoses. Seat shall be model SW2326#01.

### CODES/STANDARDS

- Meets and exceeds ASME A112.4.2, ASME A112.18.1/CSA B125.1, UL 1431, CSA C22.2 #68 and back siphonage testing to ASSE 1001 and CSA B64.1.1
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- Complies with CA Prop 65 warning requirements




### SPECIFICATIONS

<b>Power Rating</b>	AC 120 V, 60 Hz
<b>Power Consumption</b>	1023 W
<b>Max Power Consumption</b>	1131 W
<b>Power Cord Length</b>	3.9 ft (1.2 m)
<b>Spray Volume</b>	Rear Cleansing: 0.07 – 0.11 gal/min Front Cleansing: 0.07 – 0.11 gal/min
<b>Spray Features</b>	Adjustable Surface Temp: 95°F - 104°F (35°C - 40°C) Safety Device: Temperature Fuse
<b>Heated Seat Features</b>	Adjustable Surface Temp: 82°F - 97°F (28°C - 36°C) Safety Device: Temperature Fuse
<b>Water Supply Pressure</b>	Minimum: 7.25 PSI (Flowing) Maximum: 108.75 PSI (Static)
<b>Ambient Temp.</b>	32°F - 104°F (0°C - 40°C)
<b>Warranty</b>	One Year Limited Warranty
<b>Shipping Weight</b>	SW2326: 14.6 lbs
<b>Shipping Dimensions</b>	SW2326: 24-3/8" L x 21" W x 9" H

### INSTALLATION NOTES

- For use with potable water only. Do not use with recycled water.
- It is highly recommended to use a surge protector to prevent damage in the event of a power surge.
- Compatible with TOTO WASHLET+ and Non-WASHLET+ toilets, as well as most models from other manufacturers.
- This product is designed and evaluated based on the laws and technical standards of the Territory. Use outside the Territory may compromise safety and performance or violate local laws. Warranty, repairs, and technical support are not available for use outside the Territory.

### DIMENSIONS



GFCI outlet of 120V, 15amps.  
Power cord is 4' long with 3 prongs.