




DuraStyle Wall Mounted Toilet # 2537590092

| < 14 3/4 " > |



Wall Mounted Toilet	Dimension	Weight	Order number
Flush water quantity: 1.2/0.8 gal, Washdown model, Flushing rim: Closed, Outlet horizontal, Concealed fixation, Includes connecting set for SensoWash, cUPC listed: Yes			
Colors			
00 White			
Variant			
White High Gloss, Flush water quantity: 1.28/0.8 gal, WaterSense: Yes, ADA: Yes	14 3/4 "x14 "	67.902 lb	2537590092
Spare parts			
Installation Set	5 3/8 x 4 1/8 "	0.948 lb	005072
Noise reduction gasket	16 1/2 x 15 3/8 "	0.441 lb	005090
Actuator Plate A1 Plastic, Dual Flush, Trip lever type: Mechanical, Flush operation technology: Manual, Installation Type: surface mounted, Includes mounting frame, including mounting kit, Includes push rod	8 1/2 x 3/8 "	0.69 lb	WD5008
Connection Set Shower-toilets	8 5/8 x 10 1/4 "	1.543 lb	100691
Actuator Plate Actuator plates		1.102 lb	115770
Suitable products			
Shower toilet seat Number of warm air dryer options: 4 Steps, Water position adjustment: 5 Steps, Number of spray intensity options: 3 Steps, Number of spray temperature options: 4 Steps, Water position adjustment: 5 Steps, Rearwash, Frontwash, Pulsing shower spray: Oscillating, Number of user profiles: 2, Self-cleaning function, Decalcification function, Connection voltage: 220 - 240 V, Min. frequency: 50 Hz, Night light, 14 3/4 x 21 1/8 "	14 3/4 x 21 1/8 "		610200
Shower toilet seat Matches series DuraStyle, White, Slow close, Seat material type: Duroplast, Lid material type: Duroplast, Water position adjustment: 5 Steps, Number of spray intensity options: 3 Steps, Number of spray temperature options: 4 Steps, Water position adjustment: 5 Steps, Rearwash, Frontwash, Pulsing shower spray: Oscillating, Operation type: Remote control, Controller, Self-cleaning function, Decalcification function, Holiday mode, Night light, cUPC listed: No, UL: No, 14 3/4 x 21 1/4 "	14 3/4 x 21 1/4 "		611200

DuraStyle Wall Mounted Toilet # 2537590092

| < 14 3/4 " > |

In-Wall Tank & Carrier Standard Includes HDPE toilet wall-mounted outlet bend DN 90/90, Powder-coated, Installation Type: In lightweight stand construction, Installation Type: Drywall, Max. projection toilet: 24 5/8 ", Adjustable height: 9 1/2 ", Trip lever type: Mechanical, Trip lever placement: Front, Adjustable flush volumes, Flush type: Dual Flush, Insulated tank, Self-supporting, Suitable for panelling with plasterboards, 23 1/4 x 3 1/2 "	WD1022
Shower toilet seat Matches series DuraStyle, Slow close, Number of warm air dryer options: 4 Steps, Water position adjustment: 5 Steps, Number of spray intensity options: 3 Steps, Number of spray temperature options: 4 Steps, Water position adjustment: 5 Steps, Rearwash, Frontwash, Pulsing shower spray: Oscillating, Warm air dryer, Number of user profiles: 4, Self-cleaning function, Decalcification function, Energy saving mode: Adjustable, Holiday mode, Night light, 14 3/4 x 20 1/2 "	613200

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.