# TOTO<sub>®</sub>

## MW6263446CEFG

## Aimes® WASHLET®+ S5 One-Piece Toilet - 1.28 GPF

### **FEATURES**

- Concealed supply connection for seamless installation
- High-efficiency TORNADO FLUSH® system 1.28 GPF (4.8 LPF)
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces
- Completely skirted design for a sleek and understated look that's easier to clean
- **UNIVERSAL HEIGHT**
- Chrome plated trip lever
- 12" Rough-in
- Elongated front bowl and WASHLET+ S5 set
- EWATER+® auto-cleans wand after every use
- PREMIST® automatically mists the bowl before each use
- Self-cleaning wand cleans itself inside and out before and after every use
- CLEAN RESIN® keeps wand and seat cleaner, more hygienic, and effortless to maintain
- Multifunction remote control with personalized memory settings for up to 4 users
- Night light illuminates the inside of the bowl

### **MODELS**

MW6263446CEFG (#01)

With CEFIONTECT ceramic glaze, WASHLET+ S5 with contemporary design

- CST626CEFGAT40 Elongated toilet with CEFIONTECT
- SW3446 WASHLET+ S5

## **OPTIONAL COMPONENTS**

- **TSU03W.10R** 10" Unifit Rough-In
- **TSU03W.14R** 14" Unifit Rough-In
- THU311N(#BN, #PN) Trip Lever (Brushed Nickel, Polished Nickel)

#### **COLORS/FINISHES**

#01 Cotton





TORNADO FLUSH









#### PRODUCT SPECIFICATION

The one-piece high-efficiency TORNADO FLUSH system toilet shall be 1.28 GPF (4.8 LPF). Toilet shall be 12" Unifit rough-in. Toilet shall have optional CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall have elongated front bowl with Polished Chrome trip lever.

Toilet shall be TOTO Model MW6263446CEFG#01.

See SW3446 Specification Sheet for details on included WASHLET.

#### CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO (cUPC®), EPA WaterSense®, State of Massachusetts, City of Los Angeles, and
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance, and others
- ADA compliant for residential use when installed with trip lever located on the approach side
- Complies with CA Prop 65 warning requirements







#### **SPECIFICATIONS**


Water Use	1.28 GPF (4.8 LPF)
Flush System	TORNADO FLUSH®
Water Surface	7-3/4" x 9-3/8"
Trap Diameter	2-1/8"
Rough-in	12" (10" and 14" options available)
Trap Seal	2-1/8"
Warranty	One Year Limited Warranty
Material	Vitreous China
Shipping Weight	CST626CEFGAT40: 119 lbs SW3446: 15.4 lbs
Shipping Dimensions	CST626CEFGAT40 30" L x 19" W x 29-5/8" H <sup>1</sup> x 18-1/2" H <sup>2</sup> SW3446: 24-3/8" L x 17-9/16" W x 7-7/16" H

See SW3446 Specification Sheet for details on included WASHLET.

#### **INSTALLATION NOTES**

Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

#### **DIMENSIONS**

