# TOTO<sub>®</sub>

## MW7763446CEFG

## Drake® WASHLET®+ S5 Two-Piece Toilet - 1.28 GPF

## **FEATURES**

- Concealed supply connection for seamless installation
- High-efficiency TORNADO FLUSH<sub>®</sub> system 1.28 GPF (4.8 LPF)
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces.
- 12" Rough-in, supply line sold separately
- UNIVERSAL HEIGHT
- Chrome plated trip lever
- Elongated front bowl toilet and tank with WASHLET+ S5 set
- EWATER+® auto-cleans wand after every use
- PREMIST® automatically mists the bowl before each use
- Self-cleaning wand cleans itself inside and out before and after every use
- CLEAN RESIN® keeps wand and seat cleaner, more hygienic, and effortless to maintain
- Multifunction remote control with personalized memory settings for up to 4 users
- Night light illuminates the inside of the bowl

## **MODELS**

MW7763446CEFG (#01)

With CEFIONTECT ceramic glaze, WASHLET+ S5 with contemporary design

- C776CEFGT40
  - Elongated bowl with CEFIONTECT
- ST776EA
  - Tank and cover only
- SW3446
  - WASHLET+ S5

## **OPTIONAL COMPONENTS**

 THU808(#01, #03, #11, #12, #51, #BN, #PN, #PB, #RB, #MBL)-A

Trip Lever - Cotton, Bone, Colonial White, Sedona Beige, Ebony, Brushed Nickel, Polished Nickel, Polished Brass, Oil Rubbed Bronze, Matte Black

#### **COLORS/FINISHES**

#01 Cotton











## PRODUCT SPECIFICATION

The two-piece high-efficiency TORNADO FLUSH toilet shall be 1.28 GPF (4.8 LPF). UNIVERSAL HEIGHT Toilet with CEFIONTECT glaze finish. Toilet shall have high-profile tank, elongated front bowl and chrome trip lever. Toilet shall be TOTO Model MW7763446CEFG#01.

See SW3446 Specification Sheet for details on included WASHLET.

#### CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO (cUPC®), EPA WaterSense®, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance, and others
- ADA compliant for residential use when installed with trip lever located on the approach side
- Complies with CA Prop 65 warning requirements







Drake® WASHLET®+ S5 Two-Piece Toilet - 1.28 GPF

#### **SPECIFICATIONS**


Water Use	1.28 GPF (4.8 LPF)
Flush System	TORNADO FLUSH®
Min. Water Pressure	8 psi (Flowing)
Water Surface	9" x 6-7/8"
Trap Diameter	2-1/8"
Rough-in	12"
Trap Seal	2-1/8"
Warranty	One Year Limited Warranty
Material	Vitreous China
Shipping Weight	<b>C776CEFGT40:</b> 62 lbs <b>ST776EA:</b> 32 lbs <b>SW3446:</b> 15.4 lbs
Shipping Dimensions	C776CEFGT40 30-1/8" L x 15-1/4" W1 x 10-7/8" W2 x 17-3/4" H ST776EA 18-3/4" L x 8-7/8" W x 16-1/4" H SW3446 24-3/8" L x 17-9/16" W x 7-7/16" H

See SW3446 Specification Sheet for details on included WASHLET.

## **INSTALLATION NOTES**

Back-to-Back Toilet Installations:


TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

## **DIMENSIONS**

\*\*GFCI outlet of 120V, 15A
Washlet power cord is 4' long with 3 prongs.



These dimensions and specifications are subject to change without notice