

WARRANTY

Cisal Bath Collection has a limited lifetime warranty.

“Warranty Exclusion: This warranty is for normal domestic use only and excludes defect or injury caused by or resulting from misuse, abuse, neglect, accidental damage or improper installation”.

There is no warranty on the finish Tuscan Brass.

FINISH CARE

1. WIPE DOWN AFTER USE TO AVOID SPOTTING
2. USE A SOFT BRUSH FOR DETAIL CLEANING
3. DO NOT USE SPRAY CLEANERS WITH AMMONIA, ALCOHOL OR BLEACH
4. DO NOT USE ABRASIVES LIKE COMET, AJAX OR BONAMI

FINISH	CLEANING	CARE
POLISHED CHROME	50-50 VINEGAR AND WATER	FLITZ WAX OR GAGNON’S SX, SIMICHROME
INCA BRASS	50-50 VINEGAR AND WATER	DO NOT USE FLITZ – GAGNON’S SX OK
POLISHED NICKEL	50-50 VINEGAR AND WATER	FLITZ WAX OR GAGNON’S SX, SIMICHROME
SATIN NICKEL	50-50 VINEGAR AND WATER	FLITZ WAX OR GAGNON’S SX
TUSCAN BRASS	PAT DRY AFTER USE	FLITZ WAX. DO NOT RUB OR WIPE.

FOR WATER SPOTTING ON POLISHED CHROME, POLISHED NICKEL OR SATIN NICKEL, USE SIMICHROME PASTE.

FLOW RATE	
PRESSURE	FLOW
7.25 psi	0.92 gpm
14.50 psi	1.26 gpm
29.00 psi	1.76 gpm
43.50 psi	1.82 gpm
58.00 psi	1.92 gpm
72.50 psi	1.92 gpm

TECHNICAL DATA

- Minimum dynamic pressure7.25 psi
- Maximum operational pressure (static).....145 psi
- Recommended operational pressure (static)..14.5-72.5 psi (N.B.: for pressures higher than 72.5 psi we suggest the installation of a pressure reducer)
- Maximum test pressure (static).....232 psi
- Flow rate.....max. 2.5 gpm @ 60 psi