TOTO_®

CST775CSF(G)

Drake[®] Two-Piece Toilet, 1.6 GPF

FEATURES

- TORNADO FLUSH[®] system, (1.6 GPF/6.0 LPF)
- CEFIONTECT[®] ceramic glaze minimizes waste from sticking to porous, ceramic surfaces
- Round front bowl, seat sold separately
- Universal Height
- Chrome plated trip lever
- 12" Rough-in, supply line sold separately

MODELS

- CST775CSFG (#01, #03, #11, #12) With CEFIONTECT ceramic glaze without seat
- CST775CSF (#51) Same as CST775CSFG without CEFIONTECT ceramic glaze

COMPONENTS

- C775CEFG
 Round bowl with CEFIONTECT
- C775CEF Round bowl without CEFIONTECT
- **ST776SA** Tank and cover only

OPTIONAL COMPONENTS

 THU808(#01, #03, #11, #12, #51, #PN, #BN, #RB)-A Trip Lever - Cotton, Bone, Colonial White, Sedona Beige, Ebony, Polished Nickel, Brushed Nickel, Oil Rubbed Bronze)

COLORS/FINISHES

- #01 Cotton
- #03 Bone
- #11 Colonial White
- #12 Sedona Beige
- #51 Ebony (Without CEFIONTECT glaze)







PRODUCT SPECIFICATION

The two-piece TORNADO FLUSH system toilet shall be 1.6 GPF/6.0 LPF. Toilet shall have CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall have high-profile tank, round front bowl and Chrome trip lever. Toilet shall be TOTO Model CST775CSF_____.

CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC[®])
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- ADA compliant (when installed with trip lever located on the approach side)



Drake® Two-Piece Toilet, 1.6 GPF

SPECIFICATIONS

Water Use	1.6 GPF (6.0 LPF)
Flush System	TORNADO FLUSH®
Min. Water Pressure	8 psi (Flowing)
Water Surface	9" x 6-5/8"
Trap Diameter	2-1/8"
Rough-in	12"
Trap Seal	2-1/8"
Warranty	One Year Limited Warranty
Material	Vitreous China
Shipping Weight	C775CEF(G) 53 lbs. ST776SA 32 lbs.
Shipping Dimensions	C775CEF(G) 27-5/8" L x 15-1/2" W1 x 11-1/8" W2 x 18" H ST776SA 18-3/4" L x 8-7/8" W x 16-1/4" H

INSTALLATION NOTES

Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

DIMENSIONS



TOTO_®

These dimensions and specifications are subject to change without notice